
Solvent Cleaners

DX Cleaners

PPG DX Cleaners are specifically designed to remove wax, grease, silicones, road tar, engine oil, overspray, adhesives and other contaminants. DX Cleaners are packaged ready-to-use.



DX Cleaners

- DX320 - Fast Evaporating Cleaner
- DX330 - *ACRYLI-CLEAN*®
- DX394 - 1.4 Low VOC Cleaner
- DX440 - *DITZ-O*® Wax & Grease Remover

DX Cleaners

Directions for Use

DX 320 Fast Evaporating Cleaner



- DX320 Fast Evaporating Cleaner should be used as a final cleaning wash prior to painting.
- Clean the surface with DX330, DX 440 or DX394 as below prior to sanding, taping, priming, and sealing.
- DX 320 may be used to remove surface contaminants such as finger prints left after taping.
- It may be used over all O.E.M. Finishes, bare metal surfaces, and cured and dried refinish systems. Do not use DX320 on plastic or fiberglass.
- After final taping and prior to sealer or paint application, apply DX320 liberally to the surface to be cleaned. Wipe immediately with a clean white cloth. Do not allow DX320 to dry on the surface. Clean an area no larger than 2' X 2' to avoid premature drying.

DX330 ACRYLI-CLEAN® DX394 1.4 Low VOC Cleaner DX440 DITZ-O® Wax and Grease Remover



- Wash surface with soap and water before cleaning.
- Clean surface before and after sanding.
- Apply a generous amount of DX330, DX394 or DX440 with a clean white cloth or a hand held spray bottle.
- Initial application floats contaminants to the surface where the second wipe with a clean, dry cloth will remove the contaminants.
- For maximum results, wipe dry with clean white cloth in one direction only, while the surface is still wet, to eliminate smearing of contaminants.

Do not use DX320, DX330 or DX440 on plastic or fiberglass parts. Application on these surfaces can generate static build-up, which can result in flash fire.

Do not use DX440 on soluble materials like lacquer primers or topcoats.

Technical Data:

	DX320	DX330	DX394	DX440
VOC (LB/US gal.)	6.31	6.36	1.34	6.94

Important:

Caution: Wear eye and skin protection including solvent resistant gloves and safety glasses while using surface cleaning products. Use with adequate ventilation. Observe all label and MSDS precautions.

Note: Local air quality regulations may limit use of specific DX cleaners. Verify acceptability before use

See Material Safety Data Sheet and Labels for additional safety information and handling instructions.

EMERGENCY MEDICAL OR SPILL CONTROL INFORMATION (304) 843-1300; IN CANADA (514) 645-1320

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public. Products mentioned may be hazardous and should only be used according to directions, while observing precautions and warning statements listed on label. Statements and methods described are based upon the best information and practices known to PPG Industries. Procedures for applications mentioned are suggestions only and are not to be construed as representations or warranties as to performance, results, or fitness for any intended use, nor does PPG Industries warrant freedom from patent infringement in the use of any formula or process set forth herein.



PPG Automotive Refinish

World Leaders In Automotive Finishes

PPG Industries
19699 Progress Drive
Strongsville, OH 44149

PPG Canada Inc.
2301 Royal Windsor Drive
Mississauga, Ontario L5J 1K5